

DB29 Tourbillon Maxichrono

Technical specifications



DE BETHUNE

L'ART HORLOGER AU XXI^E SIÈCLE

DB29 Tourbillon Maxichrono

Technical specifications

Name: Reference: Limitation: Functions:	DB29 Tourbillon Maxichrono DB29RS1 Limited annual production of 20 Hours, Minutes, Mono-pusher chronograph with 24 hours, 60 minutes and 60 seconds counters, 30'' indicator via the
Movement:	ultra-light De Bethune tourbillon cage on the back DB2039
Type:	Mechanical hand-wound movement
Adjustments:	Winding and setting the time by means of the crown (2 positions)
	Via a push-piece integrated in the crown for the chronograph function
	Via a push-piece at 4 o'clock to open the dome on the back

Technical features of calibre DB2039

Number of parts: Jewelling: Diameter: Power reserve:	450 53 jewels 30 mm 5 days, ensured by a self-regulating twin barrel De Bethune Innovation (2004)
Specificities:	Silicon annular balance encircled by a white gold ring De Bethune Patent (2010)
	"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)
	Silicon escape wheel
	Ultra-light De Bethune 30'' tourbillon in silicon and titanium De Bethune Innovation (2008)
	"De Bethune Absolute Clutch " De Bethune Patent (2014)
Frequency:	36,000 vibrations per hour
Adornment:	Bridges mirror-polished, sandblasted and snailed by hand Steel parts polished and chamfered by hand

DE BETHUNE

Display	
Display:	5 central curved hands – Hand-polished and flamed- blued steel for hours and minutes hands and chronograph hours and seconds indicators – Chronograph minutes indicator in rose gold
Dial :	Three dimensional silver dial constructed on different levels to maximize readability. From the center to the periphery: central hours counter – hour ring – minutes ring and minutes counter – 1/10 th of second graduated outer ring for seconds counter
Case and strap	
Case material: Case diameter: Case thickness: Lugs: Crystal: Case back:	Rose gold 5N 46 mm 11,7 mm Cone shaped In sapphire crystal (hardness of 1800 Vickers) with double anti-reflective coating Screwed down open back 30'' indicator via the ultra-light De Bethune tourbillon cage and on the chronograph mechanism Sapphire crystal (hardness of 1800 Vickers) with double anti-reflective coating protected by a polished rose gold 5N dome with invisible hinge
Water resistance: Strap: Buckle:	3 ATM Extra-supple alligator leather, alligator lining Pin buckle in 5N rose gold