

## **DB28** Tourbillon

Technical specifications





## **DB28** Tourbillon

Technical specifications

DB28 To	urbillon
nce: DB28TRS	8ZN / S
ns: Hours, N	linutes, 30'' indicator via the ultra-light De Bethune
tourbillo	n cage at 6 o'clock, Power reserve situated on
the bac	k
nent: DB2019	
Mechar	ical hand-wound movement
nent: Winding position:	and setting the time by means of the crown (2 s)
ns: Hours, M tourbillo the bac nent: DB2019 Mechar nent: Winding	linutes, 30'' indicator via the ultra-light De Bethune n cage at 6 o'clock, Power reserve situated on k nical hand-wound movement and setting the time by means of the crown (2

## Technical features of calibre DB2019

Number of parts: Jewelling: Diameter: Power reserve:	282 38 jewels 30 mm 5 days, ensured by a self-regulating twin barrel De Bethune Innovation (2004)
Specificities:	Silicon escape wheel encircled with a white gold ring De Bethune Patent (2010)
	"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)
	Silicon escape wheel
	Ultra-light De Bethune 30'' tourbillon in silicon and titanium De Bethune Innovation (2008)
Frequency:	36'000 vibrations per hour
Adornment:	Black polished steel motion-work bridge and barrel bridge Ruthenium plate cover adorned with "Côtes De Bethune" Hand snailed barrels Hand-polished and chamfered steel parts

## DE BETHUNE

Display	
Display:	Hand-polished stainless steel hands
	Ultra-light De Bethune 30'' tourbillon in silicon and titanium at 6 o'clock – De Bethune Innovation (2008)
Dial :	Black in mirror-polished steel Anthracite minutes ring Black hours ring with black mirror-polished steel markers
Case and strap	
Case material: Case diameter: Case thickness: Lugs: Crystal:	Rose gold 5N 42.6 mm 9,20 mm Short or long floating lugs in polished in black zirconium De Bethune Patent (2006) In sapphire crystal (hardness of 1800 Vickers) with double anti-reflective coating
Case back:	Closed and screwed down case back in polished rose gold 5N that opens on a linear power reserve in rose gold 5N Sapphire crystal (1800 Vickers hardness) with double anti- reflective coating
Water resistance: Strap: Buckle:	3 ATM Extra-supple alligator skin, lining in alligator Buckle in black polished zirconium and ardillon in rose gold 5N