

# DE BETHUNE

L'ART HORLOGER AU XXI<sup>E</sup> SIÈCLE

## DB25 Moon Phase

Technical specifications



**DB25 Moon Phase**  
Technical specifications

Name:	DB25 Moon Phase
Reference:	DB25LRS1V1
Functions:	Hours, Minutes, Spherical moon phase indication at 12 o'clock, Power reserve situated on the back
Movement:	DB2105V1
Type:	Mechanical hand-wound movement
Adjustment:	Winding, setting the spherical moon phase and the time by means of the crown (3 positions)

**Technical features of calibre DB2105V1**

Number of parts:	305
Jewelling:	29 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	Titanium and platinum balance wheel with blom studs <i>De Bethune Patent (2008)</i>  "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i>  Silicon escape wheel  Spherical moon phase indication accurate to a degree of one lunar day every 122 years – <i>De Bethune Patent (2004)</i>  Triple <i>pare-chute</i> shock-absorbing system <i>De Bethune Innovation (2005)</i>
Frequency:	28,800 vibrations per hour
Adornment:	Silver plate and barrel bridge cover adorned with "Côtes De Bethune" Hand snailed barrels Hand-polished, chamfered steel parts

# DE BETHUNE

L'ART HORLOGER AU XXI<sup>E</sup> SIÈCLE

## **Display**

Display: Hand-polished flame-blued steel curved hands  
Spherical moon phase indication in palladium and flamed-blued steel with an accuracy of one lunar day every 122 years at 12 o'clock – De Bethune Patent (2004)

Dial : Silver-toned hand-guilloch , with 12 radiating sectors  
De Bethune star-studded sky in blued mirror-polished steel, inlaid with rose gold stars  
Silver curved hour and moon phase rings with black relief Roman numerals

## **Case and strap**

Case material: Rose gold 5N  
Case diameter: 44 mm  
Case thickness: 11,2 mm  
Lugs: Integrated, hollowed lugs  
Crystal: In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating  
Case back: Open back in polished rose gold and linear power reserve on the back  
Sapphire crystal (1800 Vickers hardness) with double anti-reflective coating  
Water-resistance: 3 ATM  
Strap: Extra-supple alligator leather, alligator lining  
Buckle: Pin buckle in rose gold 5N