



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

**DB28**

Technical specifications





**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

## **DB28**

### Technical specifications

Name:	DB28
Reference:	DB28RS8C6ZN / S
Functions:	Hours, Minutes, Spherical moon phase indication at 6 o'clock, Power reserve situated on the back, Performance indication between 2 and 3 o'clock
Movement:	DB2115V4
Type:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions) Spherical moon phase adjustment via a corrector

### **Technical features of calibre DB2115V4**

Number of parts:	297
Jewelling:	38 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration <i>De Bethune Patent (2016)</i>  "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i>  Silicon escape wheel  Spherical moon phase indication accurate to a degree of one lunar day every 122 years – <i>De Bethune Patent (2004)</i>  Triple <i>pare-chute</i> shock-absorbing system <i>De Bethune Innovation (2005)</i>
Frequency:	28,800 vibrations per hour
Adornment:	Black hand polished steel motion-work bridge Black plate and barrel bridge cover adorned with "Côtes De Bethune" Hand snailed barrels Black circular-grained power reserve decoration Hand-polished and chamfered steel parts



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

### **Display**

Display: Hand-polished stainless steel hands  
Spherical moon phase indication in palladium and flamed-blued steel with an accuracy of one lunar day every 122 years at 6 o'clock – De Bethune Patent (2004)  
Performance indicator between 2 and 3 o'clock

Dial: Mirror-polished steel hours ring  
Polished steel hour-markers  
Mirror-polished and silver-toned minutes ring

### **Case and strap**

Case material: Rose gold 5N  
Case diameter: 42.6 mm  
Case thickness: 9.30 mm  
Lugs: short or long floating lugs in polished black zirconium  
*De Bethune Patent (2006)*

Crystal: In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating

Case back: Closed and screwed down case back in polished *rose gold 5N* that opens on a linear power reserve in rose gold 5N  
Sapphire crystal (1800 Vickers hardness) with double anti-reflective coating

Water resistance: 3 ATM

Strap: Extra-supple alligator leather, alligator lining

Buckle: Pin buckle in black polished zirconium and rose gold