

DB28GS Grand Bleu Technical specifications





DB28GS Grand Bleu

Technical specifications

Name:	DB28GS Grand Bleu
Reference:	DB28GSV2Y
Functions:	Hours, Minutes, Seconds, Power reserve indication between 9 and 10 o'clock, unidirectional rotating bezel, manual dial lighting
Movement:	DB2080
Туре:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions), push button at 6 o'clock to activate the lightening

Technical features of calibre DB2080

Number of parts: Jewelling: Diameter: Power reserve:	400 51 jewels 30 mm 5 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration <i>De Bethune Patent (2016)</i>
	"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)
	Silicon escape wheel
	Triple <i>pare-chute</i> shock-absorbing system De Bethune Innovation (2005)
	Dial lighting produced by an entirely mechanical means working on the dynamo principle powered by a twin barrel and manually controlled via a pusher <i>De Bethune Innovation (2019)</i>
Frequency:	28,800 vibrations per hour
Adornment:	Mirror- polished yellow grade 5 titanium motion-work bridge Plate and barrel bridge covers in hand-smoothed yellow grade 5 titanium and adorned with " <i>Microlight</i> engraving" <i>De Bethune Innovation (2007</i>) Hand-snailed barrels Hand-polished and chamfered steel parts



Display	
Display:	Yellow titanium hours and minutes hand with inserts, luminescent tip Yellow titanium sandblasted by hand minute hand, luminescent tip Polished steel seconds hand with luminescent tip Power-reserve indicator between 9 and 10 o'clock
Dial:	Satin-brushed and yellow grade 5 titanium minutes dial with cut-out Arabic numerals Rotating bezel crystal with metallised minutes ring
Case and strap	
Case material:	Black zirconium case middle with "Microlight" decoration, yellow brushed grade 5 titanium caseback and bezel
Case diameter:	44 mm
Case thickness:	12.8 mm
Lugs:	Floating lugs in yellow brushed grade 5 titanium with yellow polished grade 5 titanium inserts – <i>De Bethune Patent (2006)</i>
Crystal:	In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating
Case back:	open in yellow brushed grade 5 titanium
Water resistance:	10 ATM
Strap:	Natural rubber strap + 1 canvas / leather strap
Buckle:	Folding clasp + pin buckle in yellow brushed grade 5 titanium