



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB Kind of Two Jumping GMT





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB Kind of Two Jumping GMT

Technical specifications

Name:	DB Kind of Two Jumping GMT
Reference:	DBK2V1
Functions:	Dual front and back display of hours and minutes, jumping seconds, Second time zone (GMT)
Movement:	DB2517
Type:	Mechanical hand-wound movement
Adjustment:	Winding, setting the time and the GMT, by means of the crown (3 positions)

Technical features of calibre DB2517

Number of parts:	394
Jewelling:	58 rubis
Diameter:	30 mm
Power reserve:	4 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	<p>Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration <i>De Bethune Patent (2016)</i></p> <p>"De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i></p> <p>Silicon escape wheel</p> <p>De Bethune Dead Beat Second <i>De Bethune Innovation (2011)</i></p> <p>GMT allowing to adjust 2 time zones, different on each side</p>
Frequency:	36,000 vibrations per hour
Adornment:	<p>Motion works bridge and concave cover plate in grade 5 titanium, mirror-polished</p> <p>Polished and chamfered barrel bridge, with shot-blasted stages</p> <p>Hand snailed barrels</p> <p>Steel parts polished and chamfered by hand</p>



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Contemporary single-sided display

Display:	Polished titanium hours and minutes indication Minute indication on the periphery Hour indication centered around the balance wheel at 6 o'clock
Dial:	Silver hour ring with polished blued index Silver colour minute ring with blue transfer

Classic reverse side display

Display:	hand-polished and blued titanium hands for hours, minutes and dead beat seconds
Dial:	Dial silvered and relief, with convex levels and guilloché central part

Case and strap

Case material:	Polished grade 5 titanium
Case diameter:	43,3 mm
Case thickness:	11,4 mm
Crown :	at noon on the front side, at 6 o'clock on the reverse side, and integrated into the case
Lugs:	Polished grade 5 titanium floating lugs – <i>De Bethune Patent (2006)</i> With case turning mechanism that can be clearly positioned on the front or back side
Crystal doubles-sides:	In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating
Water resistance:	3 ATM
Strap:	Extra-supple alligator leather, alligator lining
Buckle:	Pin buckle in polished grade 5 titanium