



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE



DB28XP

Technical specifications

Name:	DB28XP
Reference:	DB28XPTIS1
Function:	Hours, Minutes
Movement:	DB2115v6
Type:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions)

Technical features of calibre DB2115v6

Number of parts:	194
Jewelling:	29 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel – <i>De Bethune Innovation (2004)</i>



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Specificities:

Titanium balance with white gold inserts, optimised for temperature differences and air penetration –
De Bethune Patent (2016)

"De Bethune" balance-spring with flat terminal curve
De Bethune Patent (2006)

Silicon escape wheel

Triple *pare-chute* shock-absorbing system –
De Bethune Innovation (2005)

Frequency:

28,800 vibrations/hour

Adornment:

Hand-crafted finishing and decoration

Display

Display:

Polished titanium hands with polished blued titanium inserts

Dial:

Polished titanium hours ring with polished titanium spherical hour-markers

Circular satin-brushed titanium minutes ring

Polished titanium barrel bridge and triangular central bridge guards with straight-grained chamfered contours

Titanium dial base with "microlight" decoration centred on the balance – *De Bethune Innovation (2007)*

Case and strap

Case material:

Polished grade 5 titanium with "microlight" case middle

Case diameter:

43 mm

Case thickness:

7.2 mm

Lugs:

Polished grade 5 titanium floating lugs –
De Bethune Patent (2006)

Crystal:

Sapphire (1,800 Vickers hardness) with double anti-reflective coating

Caseback:

Solid, in polished grade 5 titanium

Engraved ring in blued circular satin-finish titanium

Titanium plate with "microlight" decoration and De Bethune logo

Water resistance:

3 ATM

Strap:

Extra-supple alligator leather with alligator lining

Buckle:

Grade 5 titanium buckle and pin