



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28xs Aérolite





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28xs Aérolite

Technical specifications

Name:	DB28xs Aérolite
Reference:	DB28xsZM
Function:	Hours, Minutes
Movement:	DB2005
Type:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions)

Technical features of calibre DB2005

Number of parts:	160
Jewelling:	27 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel, <i>De Bethune Innovation (2004)</i>
Specificities:	Titanium balance with white gold inserts, optimised for temperature differences and air penetration – <i>De Bethune Patent (2016)</i> "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i> Silicon escape wheel Triple <i>pare-chute</i> shock-absorbing system – <i>De Bethune Innovation (2005)</i>
Frequency:	28,800 vibrations/hour
Adornment:	Hand-crafted finishing and decoration

Display

Display:	Polished pink gold hands
Dial:	Anthracite hours and minutes ring with transferred Arabic numerals in pink Blue meteorite dial with a random guilloché dial and a starry sky with white gold stars



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Case and strap

Case material:	Mat anthracite zirconium
Case diameter:	38.7 mm
Case thickness:	7.4 mm
Lugs:	Mat anthracite zirconium floating lugs – <i>De Bethune Patent (2006)</i>
Crystal:	Sapphire (1,800 Vickers hardness) with double anti-reflective coating
Caseback:	Open, in mat anthracite zirconium and sapphire (1,800 Vickers hardness) with double anti-reflective coating Flat polished steel barrel bridge guard Plate guard in titanium with microlight decoration
Water resistance:	3 ATM
Straps:	Extra-supple alligator leather with alligator lining and black textile
Buckle:	Mat anthracite zirconium buckle and pin

