

DB25GMT Starry Varius





DB25GMT Starry Varius

Technical specifications

Name: DB25GMT Starry Varius

Reference: DB25VGR

Functions: Hours, Minutes, Second time zone (GMT),

Day/night indicator, Jumping date

Movement: DB2507

Type: Mechanical hand-wound movement

Adjustment: Winding, setting the local and travel time (GMT) by means of the

crown (3 positions) - Secure bidirectional systems Via a corrector at 6 for the date hand (clockwise)

Technical features of calibre DB2507

Number of parts: 368

Jewelling: 40 jewels

Diameter: 30 mm

Power reserve: 5 days, ensured by a self-regulating twin barrel

A De Bethune Innovation (2004)

Specificities: Titanium balance wheel with white gold inserts, optimised for temperature

differences and air penetration De Bethune Patent (2016)

"De Bethune" balance-spring with flat terminal curve

De Bethune Patent (2006)

Silicon escape wheel

Microsphere Day/night indicator in rose gold and blued steel similar decoration technic of the spherical moon phase – *De Bethune Patent*

(2004)

Triple pare-chute shock-absorbing system

De Bethune Innovation (2005)

Frequency: 28,800 vibrations per hour

Adornment: Curved mirror-polished steel plate cover

Steel barrel bridge cover, mirror-polished and adorned with "Côtes De Bethune" enhanced with microlight decoration in its center – De

Bethune innovation 2016 Hand snailed barrels

Hand-polished, chamfered steel parts



Display

Display: Hand-polished curved hands in rose gold

Hand-polished flamed-blued date hand with polished end Day/night indicator in rose gold 5N and blued steel of the microsphere – similar decoration technic of the spherical moon

phase – De Bethune Patent (2004)

date

Dial and flanges: Curved date ring in blued titanium with gold transfer

Silver curved hour ring

Rose gold curved minute ring

Silver 24h sub-dial with two-tone decals

Central dial in 2 parts: blue polished titanium with white gold pins/radiant silver microlight decoration

with a sunburst insert in polished rose gold

Case and strap

Case material: Rose gold 5N
Case diameter: 42 mm
Case thickness: 11,8 mm

Lugs: Integrated, hollowed lugs

Crystal: In sapphire crystal (1800 Vickers hardness) with double anti-reflective

coating

Case back: Open back in rose gold 5N and sapphire crystal (1800 Vickers

hardness) with double anti-reflective coating

Water-resistance: 3 ATM

Strap: Extra-supple alligator leather, alligator lining

Buckle: Pin buckle in rose gold 5N