



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

## **DB25 Moon Phase Starry Sky**

Technical specifications





**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

## **DB25 Moon Phase Starry Sky**

### Technical specifications

Name:	DB25 Moon Phase Starry Sky
Reference:	DB25sJWS1
Functions:	Hours, Minutes, Spherical moon phase indication at 12 o'clock
Movement:	DB2105
Type:	Mechanical hand-wound movement
Adjustment:	Winding, setting the spherical moon phase and the time by means of the crown (3 positions)

### ***Technical features of calibre DB2105***

Number of parts:	245
Jewelling:	27 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	Silicon annular balance encircled by a white gold ring <i>De Bethune Patent (2010)</i>  "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i>  Silicon escape wheel  Spherical moon phase indication accurate to a degree of one lunar day every 122 years – <i>De Bethune Patent (2004)</i>  Triple <i>pare-chute</i> shock-absorbing system <i>De Bethune Innovation (2005)</i>
Frequency:	28,800 vibrations per hour
Adornment:	Plate and barrel bridge cover in mirror-polished steel Hand snailed barrels Hand-polished, chamfered steel parts



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

### ***Display***

**Display:** Hand-polished flame-blued steel with white gold insert curved hands  
Spherical moon phase indication in palladium and flamed-blued steel set with 44 diamonds and 44 sapphires (sapphires 0.039 cts + diamonds 0.04 cts) with an accuracy with precision of one lunar day every 122 years at 12 o'clock – De Bethune Patent (2004)

**Dial:** De Bethune star-studded sky in blued and polished titanium with hand-fitted white gold pins and 21 diamonds (0.0927 cts) depicting the stars  
Diamond hours markers

### ***Case and strap***

**Case material:** White gold set with 61 baguette-cut diamonds (4.34 cts)  
**Case diameter:** 40 mm  
**Case thickness:** 11,7 mm  
**Lugs:** Integrated, hollowed lugs  
**Crystal:** In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating  
**Case back:** Open back in polished white gold and linear power reserve on the back  
Sapphire crystal (1800 Vickers hardness) with double anti-reflective coating  
**Water-resistance:** 3 ATM  
**Strap:** Extra-supple alligator leather, alligator lining  
**Buckle:** Pin buckle in white gold