



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28

Technical specifications





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28

Technical specifications

Name:	DB28
Reference:	DB28TIS8C6PN /S
Functions:	Hours, Minutes, Spherical moon phase indication at 6 o'clock, Power reserve situated on the back, Performance indication between 2 and 3 o'clock
Movement:	DB2115V4
Type:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions) Spherical moon phase adjustment via a corrector

Technical features of calibre DB2115V4

Number of parts:	297
Jewelling:	38 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities:	Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration <i>De Bethune Patent (2016)</i> "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i> Silicon escape wheel Spherical moon phase indication accurate to a degree of one lunar day every 122 years – <i>De Bethune Patent (2004)</i> Triple <i>pare-chute</i> shock-absorbing system <i>De Bethune Innovation (2005)</i>
Frequency:	28,800 vibrations per hour
Adornment:	Black hand-polished steel motion-work bridge Black plate and barrel bridge cover adorned with "Côte De Bethune" Hand snailed barrels Black circular-grained power reserve decoration Hand-polished and chamfered steel parts



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Display

Display:	Hand-polished stainless steel hands Spherical moon phase indication in palladium and flamed-blued steel with an accuracy of one lunar day every 122 years at 6 o'clock – De Bethune Patent (2004) Performance indicator between 2 and 3 o'clock
Dial:	Blued mirror-polished steel hours ring Polished steel hour-markers Silver silken minutes ring

Case and strap

Case material:	Mirror-polished grade 5 titanium
Case diameter:	42.6 mm
Case thickness:	9.30 mm
Lugs:	Short or long floating lugs in mirror-polished grade 5 titanium – <i>De Bethune Patent (2006)</i>
Crystal:	In sapphire crystal (hardness of 1800 Vickers) with double anti-reflective coating
Case back:	Screwed down back in polished grade 5 titanium that opens on a linear power reserve in rose gold 5N Sapphire crystal (hardness of 1800 Vickers) with double anti-reflective coating
Water resistance:	3 ATM
Strap:	Extra-supple alligator leather, alligator lining
Buckle:	Pin buckle in mirror-polished grade 5 titanium