



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

**DB28 Digitale**  
Technical specifications





**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

## **DB28 Digitale**

### Technical specifications

Name:	DB28 Digitale
Reference:	DB28DN / S
Functions:	Jumping hours, Minutes, Spherical moon phase indication in the center
Movement:	DB2144
Type:	Mechanical hand-wound movement
Adjustment:	Winding, setting the spherical moon phase and the time by means of the crown (3 positions)

### ***Technical features of calibre DB2144***

Number of parts:	355
Jewelling:	32 jewels
Diameter:	30 mm
Power reserve:	5 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>

Specificities:	Silicon annular balance encircled by a white gold ring <i>De Bethune Patent (2010)</i>
----------------	---

"De Bethune" balance-spring with flat terminal curve  
*De Bethune Patent (2006)*

Silicon escape wheel

Spherical moon phase indication accurate to a degree of one lunar day every 1112 years – *De Bethune Patent (2004)*

Blued triple pare-chute shock-absorbing system  
*De Bethune Innovation (2005)*

Frequency:	28,800 vibrations per hour
------------	----------------------------

Adornment:	Silver plate and barrel bridge covers adorned with "Côtes De Bethune" Hand snailed barrels Hand-polished, flame-blued and chamfered steel parts
------------	--



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

### ***Display***

Display:	Jumping-hour aperture at 12 o'clock Analogue minutes indicator on a rotating disc Spherical moon phase indication in palladium and flamed-blued steel accurate to a degree of one lunar day every 1112 years at the center – De Bethune Patent (2004)
Dial:	Silver-toned hand-guilloché barley-corn motif Polished steel minute-markers at 12 o'clock on a De Bethune star-studded sky in blued and polished titanium, with hand-fitted white gold stars depicting the stars Silver-toned minutes and hours disc

### ***Case and strap***

Case material:	Mirror-polished grade 5 titanium
Case diameter:	45 mm
Case thickness:	11,6 mm
Lugs:	Short or long floating lugs in mirror-polished grade 5 titanium – <i>De Bethune Patent (2006)</i>
Crystal:	In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating
Case back:	Screwed down open back in polished grade 5 titanium and sapphire crystal (1800 Vickers hardness) with double anti-reflective coating
Water resistance:	3 ATM
Strap:	Extra-supple alligator leather, alligator lining
Buckle:	Pin buckle in mirror-polished grade 5 titanium