



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28XS KIND OF BLUE TOURBILLON

Technical specifications





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28XS KIND OF BLUE TOURBILLON

Technical specifications

| | |
|-------------|--------------------------------------------------------------------------------------------|
| Name: | DB28xs Kind of Blue Tourbillon |
| Reference: | DB28XSTB |
| Function: | Hours, Minutes, 30'' indicator via the ultra-light De Bethune tourbillon cage at 6 o'clock |
| Movement: | DB2009v5 |
| Type: | Mechanical hand-wound movement |
| Adjustment: | Winding and setting the time by means of the crown (2 positions) |

Technical features of calibre DB2009v7

| | |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of parts: | 238 |
| Jewelling: | 36 jewels |
| Diameter: | 30 mm |
| Power reserve: | 5 days, ensured by a self-regulating twin barrel, De Bethune Innovation (2004) |
| Specificities: | <p>Titanium balance with white gold inserts, optimised for temperature differences and air penetration De Bethune Patent (2016)</p> <p>"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)</p> <p>Silicon escape wheel</p> <p>Ultra-light De Bethune 30'' tourbillon in titanium De Bethune Innovation (2008)</p> |
| Frequency: | 36,000 vibrations per hour |
| Adornment: | Hand-crafted finishing and decoration |



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Display

| | |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display: | Polished titanium hands |
| Dial: | Titanium hour ring with blued microlight decoration and polished hour markers. Blued grade 5 circular satin titanium minutes and seconds ring Bridge cover on the barrel and triangular central bridge in grade 5 blued polished titanium with blued drawn chamfered contour. |

Case and strap

| | |
|-------------------|----------------------------------------------------------------------------------|
| Case material: | Blued polished grade 5 |
| Case diameter: | 38.7 mm |
| Case thickness: | 8 mm |
| Lugs: | Blued polished grade 5 titanium floating lugs De Bethune Patent (2006) |
| Crystal: | Sapphire (1800 Vickers hardness) with double anti-reflective coating |
| Caseback: | Screwed case back in blued polished titanium with double anti-reflective coating |
| Water resistance: | 3 ATM |
| Strap: | Extra-supple alligator leather with alligator lining |
| Buckle: | Blued grade 5 titanium buckle and pin |