



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB KIND OF TWO JUMPING GMT

Technical specifications



DB KIND OF TWO JUMPING GMT

Technical specifications

Name :	DB Kind of Two Jumping GMT
Reference :	DBK2V1S8
Functions :	Dual front and back display of hours and minutes, jumping seconds, Second time zone (GMT)
Movement :	Calibre 2517
Type :	Mechanical hand-wound movement
Adjustment :	Winding, setting the time and the GMT, by means of the crown (3 positions)

Technical features of calibre 2517

Number of parts :	394
Jewelling :	58 rubis
Diameter :	30 mm
Power reserve :	4 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i>
Specificities :	Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration <i>De Bethune Patent (2016)</i> "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i> Silicon escape wheel De Bethune Dead Beat Second <i>De Bethune Innovation (2011)</i> GMT allowing to adjust 2 time zones, different on each side
Frequency :	36'000 vibrations per hour
Adornment :	Motion works bridge and concave cover plate in grade 5 titanium, mirror-polished Polished and chamfered barrel bridge, with shot-blasted stages Hand snailed open worked barrels Steel parts polished and chamfered by hand



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Contemporary single-sided display

Display :	Polished titanium hours and minutes indication Minute indication on the periphery Hour indication centered around the balance wheel at 6 o'clock
Dial :	Silver colour hour ring with polished blued index Silver colour minute ring with blue transfer

Classic reverse side display

Display :	Hand-polished rose gold hour and minute hands Polished titanium jumping seconds hand
Dial :	Anthracite dial with 5N transfer, with convex levels and guilloché central part

Case and strap

Case material :	Polished grade 5 titanium
Case diameter :	43,3 mm
Case thickness :	11,4 mm
Crown :	at noon on the front side, at 6 o'clock on the reverse side, and integrated into the case
Lugs :	Polished Grade 5 titanium floating lugs <i>De Bethune Patent</i> (2006) With case turning mechanism that can be clearly positioned on the front or back side
Crystal double-sides :	In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating
Water resistance :	3 ATM
Strap :	Extra-supple alligator leather, alligator lining
Buckle :	Pin buckle in polished grade 5 titanium