



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28xs SeaTourbillon





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28xs Sea Tourbillon

Technical specifications

Name:	DB28xs SeaTourbillon
Reference:	DB28xsT
Functions:	Hours, Minutes, 30" indicator via the ultra-light De Bethune tourbillon cage at 6 o'clock
Movement:	DB2009v7
Type:	Mechanical hand-wound movement
Adjustment:	Winding and setting the time by means of the crown (2 positions)

Technical features of calibre DB2009v7

Number of parts:	239
Jewelling:	33 jewels
Diameter:	30 mm
Power reserve:	5 days, ensured by a self-regulating twin barrel, De Bethune Innovation (2004)
Specificities:	Titanium balance with white gold inserts, optimised for temperature differences and air penetration De Bethune Patent (2016)
	"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)
	Silicon escape wheel
	Ultra-light De Bethune 30" tourbillon with titanium De Bethune Innovation (2008)
Frequency:	36,000 vibrations per hour
Adornment:	Handcrafted finishes and decorations



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Display

Display:	Polished titanium hands
Dial:	Titanium hour ring with blued microlight decoration and polished hour markers. Blued grade 5 circular satin titanium minutes and seconds ring Barrel bridge cover and triangular central bridge in blued grade 5 titanium with random guilloché and drawn chamfered contours.

Case and strap

Case material:	Polished grade 5 titanium
Case diameter:	38.7 mm
Case thickness:	8 mm
Lugs:	Polished grade 5 titanium floating lugs De Bethune Patent (2006)
Crystal:	Sapphire (1800 Vickers hardness) with double anti-reflective coating
Caseback:	Screwed case back in polished titanium with Sapphire (1800 Vickers hardness) double anti-reflective coating
Water resistance:	3 ATM
Strap:	Extra-supple alligator leather with alligator lining
Buckle:	polished grade 5 titanium pin buckle