



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB25 Monopusher Chronograph





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB25 Monopusher Chronograph

Technical specifications

Name :	DB25 Monopusher Chronograph
Reference :	DB25VxsS2
Functions :	Hours, minutes, chronograph monopusher button with 60 s seconds counter and 60 min instantaneous minute counter
Movement :	DB3000
Type :	Mechanical manual-winding calibre
Adjustment :	Winding and setting the time by means of the crown (2 positions) Monopusher button integrated in the crown for chronograph functions

Technical features of calibre DB3000

Number of parts :	296
Jewelling :	31 jewels
Diameter :	30 mm
Power reserve :	60 hours
Specificities :	Titanium balance wheel with white gold inserts, optimized for temperature differences and air penetration <i>De Bethune Patent (2016)</i> "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i> Silicon escape wheel
Frequency :	28'800 vibrations per hour
Adornment :	All steel components are hand-bevelled and hand-polished Steel chronograph bridges, hand-bevelled with flat polished surfaces Hand-snailed barrels Handmade finishing decorations



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Display

Display : Hour, minute, second, and minute counter hands in blued polished titanium

Dial: Salmon, radiating guilloché 12 sectors. Blue arabic numbers. Indication of the 60-minute counter by a salmon barley grain engine-turned sub-dial at 6 o'clock.

Case and strap

Case material : Polished grade 5 titanium

Case diameter : 40.6 mm

Case thickness : 9,15 mm

Lugs : Integrated and openwork lugs

Crystal : Sapphire crystal (1800 Vickers hardness), with double anti-reflective coating

Case back : Open, polished grade 5 titanium screw-down back
Sapphire crystal (1800 Vickers hardness), with double anti-reflective coating

Water-resistance : 3 ATM

Strap : Extra-supple alligator leather, alligator lined

Buckle : Pin buckle in grade 5 titanium