



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

**DB25XS SAND WINDS**





**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

## **DB25XS SAND WINDS**

### **Technical specifications**

Name:	DB25Vxs Starry Varius
Reference:	DB25VxsTiV2S5
Functions:	Hours, Minutes
Movement:	DB2005
Type:	Mechanical manual-winding calibre
Adjustment:	Winding and setting the time by means of the crown (2 positions)

### **Technical features of calibre DB2005**

Number of parts:	160
Jewelling:	27 jewels
Diameter:	30 mm
Power reserve:	6 days, ensured by a self-regulating twin barrel De Bethune Innovation (2004)
Specificities:	Titanium balance wheel with white gold inserts, optimised for temperature differences and air penetration De Bethune Patent (2016)
	"De Bethune" balance-spring with flat terminal curve De Bethune Patent (2006)
	Silicon escape wheel
	Triple pare-chute shock-absorbing system De Bethune Innovation (2005)
Frequency:	28,800 vibrations per hour
Adornment:	Silver plate and barrel bridge cover adorned with "Côtes De Bethune" Hand-snailled barrels Hand-polished, chamfered steel parts



**DE BETHUNE**

L'ART HORLOGER AU XXI<sup>e</sup> SIÈCLE

### **Display**

Display: Hands in hand-polished brown titanium

Dial : Random guilloché yellow titanium dial with white gold inserts  
Yellow titanium hours and minutes ring with brown polished titanium hour markers

### **Case and strap**

Case material: Polished grade 5 titanium

Case diameter: 40.6 mm

Case thickness: 8,8 mm

Lugs: Integrated, hollowed lugs

Crystal: In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating

Case back: Open case back in polished grade 5 titanium  
Sapphire crystal (1800 Vickers hardness) with double anti-reflective coating

Water-resistance: 3 ATM

Strap: Extra-supple alligator leather, alligator lining

Buckle: Pin buckle in grade 5 titanium